120×120×38 mm





General Specifications

· Material ······ Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)

· Expected life ······ See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60°C,

rated voltage)

· Motor protection function ······ Locked rotor burnout protection, Reverse polarity protection

For details, please refer to p. 547.

· Dielectric strength · · · · · 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)

· Insulation resistance·············· 10 MΩ or more with a 500 VDC megger (between lead wire conductors and frame)

· Sound pressure level (SPL) · · · · · At 1 m away from the air inlet

· Lead wire ······· ⊕Red ⊝Black (Sensor) Yellow

• Mass ----- 355 g

This fan can be used in environments with oil mist.*

* Environment where cutting oil creates oil mist. Conduct a product evaluation with the type of oil to be used

Specifications

The models listed below have ribs and pulse sensors.

Ī	Model no.	Rated voltage	Operating voltage range	Rated current	Rated input	Rated speed	Max. airflow		Max. static pressure		SPL	Operating temperature	Expected life
		[V]	[V]	[A]	[W]	[min ⁻¹]	[m³/min]	[CFM]	[Pa]	[inchH2O]	[dB (A)]	[°C]	[h]
	9WF1224H101	24	20.4 to 27.6	0.32	7.68	3100	3.34	118	100	0.4	46	-20 to +70	40000/60°C


The following sensor and control options are available for selection.

Available for all models. Without sensor Lock sensor

Airflow - Static Pressure Characteristics


9WF1224H101 With pulse sensor


Operating voltage range













Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)





Options

Finger guards

page: p. 533

Model no.: 109-019E, 109-019K, 109-019C, 109-019H







Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sanyo Denki:

9WF1224H101 9WF1224H102 9WF1224H1D01



